

R1-W



SOIL TECH ELITE R1-W

The Soil Tech Elite R1-W features a highly versatile multi-angle tread design. The steep angle at the center of the lug provides long tread wear, exceptional mud clearing capability and smooth roading. The shallow angle at the shoulder delivers superior traction and improved hillside stability.

Engineered for:
Farm Tractors



Size	Alt Size	Type	Rim	O.D.	S.W.	T.D.	RC	Gross Flat Plate	Infl. P.	LCC (lbs)	LI/SS
				in	in	32nds	in	sq in	psi	25/30 mph	
				mm	mm	mm	mm	sq cm	KPa	40/50 kph	
280/85R24	11.2R24	TL	W10.00	42.9	11.4	52	128	128	23	2680	115A8/B
				1089	290	41	3251	827	160	1215	
320/85R24	12.4R24	TL	W11.00	45.7	12.6	53	136	158	23	3300	122A8/B
				1161	320	42	3454	1021	160	1500	
340/85R24	13.6R24	TL	W12.00	46.9	14.0	55	140	174	23	3640	125A8/B
				1191	356	44	3555	1123	160	1650	
380/85R24	14.9R24	TL	W12.00	49.6	15.4	55	148	206	23	4300	131A8/B
				1260	390	44	3759	1328	160	1950	
420/85R24	16.9R24	TL	W15.00	51.8	17.1	59	156	243	23	5080	137A8/B
				1315	434	47	3962	1566	160	2300	
340/85R28	13.6R28	TL	W12.00	51.0	13.9	53	152	185	23	3860	127A8/B
				1295	353	42	3860	1191	160	1750	
380/85R28	14.9R28	TL	W13.00	53.3	15.1	55	160	217	23	4540	133A8/B
				1354	383	44	4063	1403	160	2060	
420/85R28	16.9R28	TL	W15.00	56.0	17.6	59	168	156	23	5360	139A8/B
				1422	447	47	4266	1654	160	2430	
380/85R30	14.9R30	TL	W13.00	55.6	15.1	55	166	230	23	4800	135A8/B
				1412	383	44	4216	1484	160	2180	
420/85R30	16.9R30	TL	W15.00	58.3	17.3	64	174	264	23	5520	140A8/B
				1481	439	51	4419	1702	160	2500	
460/85R30	18.4R30	TL	W16.00	60.7	18.5	66	182	306	23	6400	145A8/B
				1542	470	52	4622	1974	160	2900	
420/85R34	16.9R34	TL	W15.00	62.0	17.4	65	186	280	23	5840	142A8/B
				1575	442	52	4724	1804	160	2650	
460/85R34	18.4R34	TL	W15.00	64.6	18.3	66	194	325	23	6800	147A8/B
				1641	465	52	4927	2094	160	3075	
420/85R38	16.9R38	TL	W16.00	65.9	17.9	66	198	295	23	6150	144A8/B
				1674	455	52	5028	1906	160	2800	
460/85R38	18.4R38	TL	W16.00	69.1	18.8	66	206	343	23	7150	149A8/B
				1755	477	52	5231	2213	160	3250	
520/85R38	20.8R38	TL	W18.00	73.0	21.4	68	218	409	23	8550	155A8/B
				1854	543	54	5536	2638	160	3785	
520/85R42	20.8R42	TL	W18.00	77.2	21.1	69	230	435	23	9100	157A8/B
				1961	536	55	5841	2808	160	4125	
650/65R38	-	TL	DW20B	71.3	25.5	73	213	438	23	9900	160A8/157D
				1810	648	58	5409	2825	160	4500	