

L5S



UGM SLICK

Extra deep L5S design provides highest resistance to wear and cutting. Specifically designed to maximize service life in the harshest applications. Extra deep, smooth tread provides longest tire life and lowest cost-per-hour. Deep undertread for improved puncture resistance. Reinforced bead, shoulder and sidewall. Specialized mining compound for increased cut and impact resistance.

Engineered for:
Underground Mining \ Loaders



Size	Rating	Type	Rim	O.D.	S.W	T.D.	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in	in	32nds	psi	5 mph	
				mm	mm	mm	KPa	10 kph	
18.00R25	**	TL	13.00/2.5	65.7	20.1	110	120	35300	204A2
				1668	510	87	825	16000	
17.5R25	**	TL	14.00/1.5	54.9	17.5	86	94	18700	182A2
				1394	444	68	650	8500	
20.5R25	**	TL	17.00/2.0	60.9	20.9	93	94	25400	193A2
				1547	531	74	650	11500	
23.5R25	**	TL	19.50/2.5	65.6	23.8	101	94	32000	201A2
				1666	604	80	650	14500	
26.5R25	**	TL	22.00/3.0	70.6	26.9	113	94	40800	209A2
				1793	683	90	650	18500	
29.5R25	**	TL	25.00/3.5	75.6	30.6	122	94	49400	216A2
				1920	777	97	650	22400	
29.5R29	**	TL	25.00/3.5	79.1	31.5	129	94	52000	218A2
				2009	800	102	650	23600	