

E2/G2/L2



POWER MAXX+

Aggressive R4-style pattern designed to maximize traction in soft underfoot conditions. Ideal for use on graders, loaders, and earthmovers. Heavy duty bias construction maximizes traction and flotation. Wear and cut resistant tread compound. Self-cleaning tread design.

Engineered for:
Loaders \ Dump Trucks \ Graders



Size	PR	Type	Rim	O.D.	S.W	T.D.	Infl. P.	L.C.C.	Infl. P.	L.C.C.	L.I.
				in	in	32nds	psi	5 mph	psi	30 mph	
				mm	mm	mm	KPa	10 kph	KPa	50 kph	
15.5-25	12	TL	12.00/1.3	50.4	15.7	30	58	12300	36	7150	149B/168A2
				1280	399	24	400	5600	250	3250	
17.5-25	12	TL	14.00/1.5	53.3	17.2	31	51	13600	33	8050	153B/171A2
				1354	437	25	350	6150	225	3650	
	16			53.3	17.2	31	69	16100	44	9350	158B/177A2
				1354	437	25	475	7300	300	4250	
20.5-25	12	TL	17.00/2.0	58.5	20.6	35	36	14800	29	9900	160B/174A2
				1486	523	28	250	6700	200	4500	
	16			58.5	20.6	35	51	18200	40	12000	167B/181A2
				1486	523	28	350	8250	275	5450	

