

E4/L4



HAULER GRIP

Deep E4/L4 lug pattern combines excellent traction and high resistance to wear and cutting. Specifically designed to minimize vibration at haul speeds and provides the lowest cost-per-hour. Excellent traction in all off-road conditions. Deep undertread for improved puncture resistance. High quality carcass allows for excellent retreadability. Wear and cut resistant tread compound. Wide, flat footprint profile for maximum stability and wear.

Engineered for:
Loaders \ Dump Trucks



Size	Rating	Type	Rim	O.D.	S.W	T.D.	Tread Compound	TMPH	Infl. P.	L.C.C. (lbs/kg)	Infl. P.	L.C.C. (lbs/kg)	L.I.	
				in	in	32nds			psi	5 mph	psi	30 mph		
				mm	mm	mm					KPa	10 kph	KPa	50 mph
23.5R25	**	TL	19.50/2.5	65.2	23.7	66	Standard	148	94	32000	76	20400	201A2/185B	
				1656	602	52	Cut Resistant	100	650	14500	525	9250		
26.5R25	**	TL	22.00/3.0	69.9	26.7	70	Standard	173	94	40800	76	25400	209A2/193B	
				1775	678	56	Cut Resistant	113	650	18500	525	11500		
29.5R25	**	TL	25.00/3.5	75.1	30.0	75	Standard	186	94	49400	76	30900	216A2/200B	
				1907	762	60	Cut Resistant	134	650	22400	525	14000		

